



HEYD BESTELL-No.	GRÖSSE/SIZE				Abmessungen in mm / Dimensions in mm									kg/Stück
	d1	a	b	c	d1	d2	d3	d4	d7	e	l	α		
AH39-2A-35x40 -01	35	25	33	115	35,5	62	22	M28x1,5 R	M18x1,5	80	26	45°	1,330	
AH39-2A-35x40 -02	35	25	33	115	35,5	62	22	M28x1,5 L	M18x1,5	80	26	45°	1,330	
AH39-2A-40x40 -01	40	28	37	120	40,7	69	26	M30x1,5 R	M20x1,5	80	30	45°	1,800	
AH39-2A-40x40 -02	40	28	37	120	40,7	69	26	M30x1,5 L	M20x1,5	80	30	45°	1,800	
AH39-2A-50x45 -01	50	30,5	44	135	47	80	30	M30x1,5 R	M24x1,5	85	34	45°	3,000	
AH39-2A-50x45 -02	50	30,5	44	135	47	80	30	M30x1,5 L	M24x1,5	85	34	45°	3,000	
AH39-2A-65x45 -01	65	40,5	56,5	160	66	105	38	M38x1,5 R	M30x1,5	95	42	45°	5,550	
AH39-2A-65x45 -02	65	40,5	56,5	160	66	105	38	M38x1,5 L	M30x1,5	95	42	45°	5,550	

Lagerpaarung: Stahl / Stahl R (-01) = Rechtsgewinde / right hand thread (RH)
 Bearing design: steel / steel L (-02) = Linksgewinde / left hand thread (LH)