



HEYD	GRÖßE / SIZE		Abmessungen in mm / Dimensions in mm											
BESTELL-No.	d1	a	b	c	d1	d2	d3	d4	d6	e	h	l	α	kg/Stück
AH85-1-55x26 -01	55	125	100	150	55	85	15	M38x1,5 R	35	100	24	68	26°	3,200
AH85-1-55x26 -02	55	125	100	150	55	85	15	M38x1,5 L	35	100	24	68	26°	3,200
AH85-2-55x26 -01	55	140	115	150	55	85	17	M38x1,5 R	35	100	24	68	26°	3,300
AH85-2-55x26 -02	55	140	115	150	55	85	17	M38x1,5 L	35	100	24	68	26°	3,300
AH85-1-62x26 -01	62	145	115	160	62	95	17	M38x1,5 R	34	100	24	80	26°	3,900
AH85-1-62x26 -02	62	145	115	160	62	95	17	M38x1,5 L	34	100	24	80	26°	3,900
AH85-1-70x26 -01	70	160	130	160	70	110	19	M38x1,5 R	45	95	30	90	26°	4,900
AH85-1-70x26 -02	70	160	130	160	70	110	19	M38x1,5 L	45	95	30	90	26°	4,900
AH85-1-80x20 -01	80	185	152	200	78,5	120	21	M48x1,5 R	50	120	35	105	20°	8,000
AH85-1-80x20 -02	80	185	152	200	78,5	120	21	M48x1,5 L	50	120	35	105	20°	8,000
AH85-1-90x26 -01	90	190	152	200	90	135	21	M48x1,5 R	42	105	24	114	26°	10,700
AH85-1-90x26 -02	90	190	152	200	90	135	21	M48x1,5 L	42	105	24	114	26°	10,700

Lagerpaarung: Gummi-Metall-Verbindung
Bearing design: Rubber-metal-connection

R (-01) = Rechtsgewinde / right hand thread (RH)
L (-02) = Linksgewinde / left hand thread (LH)